DuPont™ FlexWrap™ EZ

Versatile Self-Adhered Flashing for Non-Flanged Objects

OVERVIEW

Description

DuPont™ FlexWrap™ EZ is a flexible, extendable self-adhered tape with a 100% butyl-based adhesive layer that helps create an air and water-tight seal around penetrations of all different shapes and sizes. **FlexWrap™ EZ** provides an option for home builders, trade contractors and remodelers to easily seal around non-flanged objects that penetrate the building envelope.

Suitable for both residential and commercial applications, **FlexWrap™ EZ** is ideal for flashing around many smaller wall protrusions like plumbing and HVAC components, vents, wires, exterior electrical outlets, exterior lights, exhaust fans, dryer vents, hose bibs, gas lines and more – a fast and easy solution to help improve energy efficiency and the durability of a wall system.



Features and Benefits

- **Application and Service Temperature:** 100% butyl adhesive performs through temperatures as low as 25 °F (-4 °C) to create a lasting airtight seal. Withstands up to 9 months (270 days) of UV exposure.
- **High Performance Durability:** Does not contain asphaltic /bitumen adhesive materials prohibited by many window manufacturers due to adverse material reactions. Adheres to most common building materials.
- **Efficiency:** Just one roll completely covers and improves the energy efficiency of an average-sized home.
- **Ease of Use:** Easy to install around penetrations of all shapes and sizes. Features a 2-piece, heavy-duty, scored release paper.

Complete System

- DuPont™ FlexWrap™ EZ is a part of a complete DuPont™ Tyvek® Building Envelope Solution that helps to improve the energy efficiency and durability of buildings.

Warranty

- DuPont™ FlexWrap™ EZ is backed by 10-Year Limited Warranties when installed as part of the Tyvek® WRB system. For more information, refer to Warranty section of the applicable DuPont Installation Guideline.

Standard Sizes

Standard Sizes for DuPont™ FlexWrap™ EZ

Unit	Width	Length	Units per Case	Cases per Pallet	Units per Pallet
Roll	2 3/4 in.	15 ft.	16	24	384

TESTING AND CODE COMPLIANCE

DuPont™ FlexWrap™ EZ exhibits physical properties as indicated below when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-833-338-7668 when additional guidance is required for writing specifications that include this product.

TEST METHOD	TEST TITLE	PROPERTY	RESULTS
AIR			

ASTM E1677	Standard Specification for Air Barrier (AB) Material or Assemblies for Low-Rise Framed Building Walls	Assembly Air Leakage	< 0.04 cfm/ft^2 (0.2 L/s • m^2)
ASTM E2357	Standard Test Method for Determining Air Leakage Rate of Air Barrier Assemblies	Assembly Air Leakage	< 0.04 cfm/ft^2 (0.2 L/s • m^2)
WATER			
ASTM E331	Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference	Installed System Water Intrusion Testing.	NO leakage at 300 Pa (6.24 psf)
ASTM E331	Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference	Installed System Water Intrusion Testing (after thermal aging (0-120°F)	NO leakage at 300 Pa (6.24 psf)
ASTM E96	Standard Test Methods for Gravimetric Determination of Water Vapor Transmission Rate of Materials	Water Vapor Permeability	< 1 perm (< 60 ng/Pa.sec.m^2)
GENERAL			
AAMA 711	Specification for Self-Adhering Flashing Used for Installation of Exterior Wall Fenestration Products	Dupont Flashing Systems Products Meet the AAMA 711 Material Standard at the Highest Classification Levels	Class A (no primer) Level 3 Thermal Exposure (80°C/176°F for 7 days)

Note:- *Tested in a wall assembly containing a window. Consult DuPont for primer recommendations

INSTALLATION

Use Conditions

- DuPont™ FlexWrap™ EZ should be installed on clean, dry surfaces that are free of frost. Wipe surfaces to remove moisture, dirt, grease and other debris that could interfere with adhesion.
- DuPont™ FlexWrap™ EZ perform best when installed at temperatures above 25 °F (–4 °C). (Consult DuPont for primer recommendations)
- DuPont™ FlexWrap™ EZ is not intended to be used for through-wall flashing applications.

Installation

- Priming is generally not required for adhering DuPont™ FlexWrap™ EZ to most common building materials. However, adverse weather conditions or cold temperatures may require use of a primer to promote adhesion. Additionally, concrete, masonry, and glass mat exterior gypsum sheathing require the use of a chemically compatible adhesive/primers.

For more information, visit us at
building.dupont.com
or call us at 1-833-338-7668

NOTICE:
Issue Date:

Print Date: 7/07/2025